

# SEAMLESS-ABSOLUTE RATED

## Specifications

- **Available Materials**  
Polypropylene
- **Seamless Construction**
- **Maximum Operating Temperature**  
160° F (71° C)
- **Suggested Differential Pressure**  
35 PSIG maximum – dirty  
10-15 PSIG optimum change out
- **Absolute (98%) Micron Rating**  
3, 5, 10, 25, 35, 50, 75, 100
- **Sizes**  
#1: 7" x 16" (17.8 cm x 40.65 cm)  
#2: 7" x 32" (17.8 cm x 81.3 cm)
- **Plastic PolyLoc® Rings**
- **Available with NSF Standard 61 Certification**

### BOS Filter Bags

#### Item # BOS5PM2P

<b>Code</b>	BOS = Polymicro seamless
<b>Micron Rating</b>	See specifications
<b>Cover</b>	PM = Polypropylene
<b>Size</b>	1, 2
<b>Ring</b>	P = Polypropylene PolyLoc®

#### Item # BOS5PP2P61

<b>Code</b>	BOS = Polymicro seamless
<b>Micron Rating</b>	See specifications
<b>Cover</b>	PP = Special NSF Construction
<b>Size</b>	2
<b>Ring</b>	P = Polypropylene PolyLoc®
<b>Suffix</b>	61 = NSF 61 Certified