

FELT FILTER BAGS

Specifications

- **Available Materials**
Polypropylene, Polyester Standard and FDA Compliant Polyester

Polypropylene and Polyester Extended Life
- **Maximum Operating Temperature**
Polypropylene: 200-220° F (93-104° C)
Polyester: 275-325° F (135-162° C)
- **Suggested Differential Pressure**
35 PSIG maximum — dirty
10-15 PSIG optimum change out
- **Micron Rating**
BPONG = 1, 3, 5, 10, 25, 50, 100
BPENG = 1, 3, 5, 10, 25, 75, 100, 200
BPOEX = 5, 10, 25, 50 100
BPEEX = 1, 5, 10, 25, 50, 100
- **Sizes**
#1: 7" x 16" (17.78 cm x 40.65 cm)
#2: 7" x 32" (17.8 cm x 81.3 cm)
- **Plastic PolyLoc® Rings**
- **Welded Seam Construction**

Polyweld® Filter Bags

Item # **BPONG100P2PWE**

Type of Filter	B = Filter Bag	
Material	Standard: PONG = Polypropylene PENG = Polyester	Extended Life: POEX = Polypropylene PEEX = Polyester
Micron Rating	See specifications	See specifications
Cover	P = Plain (no cover)	
Size	1, 2	
Ring	P = Polypropylene PolyLoc® PE = Polyester PolyLoc®	
Suffix	WE = Welded Seam Construction F = FDA Compliant Polyester	